



CARBON FIBER™, REEF™,
REFLEX MQ™, TREXX™, TWEED™,
ULTIMATE SS™, & WICKER WORX™



Spradling International
MARINE

Content

Vinyl

Backing

Hi-Loft²™

Finish

Acrylic Topcoat

Characteristics

Mildew Resistance

Antibacterial

Pink Stain Resistance

Anti-Static

Sulfide Stain Resistance

Performance

Superior Abrasion

Wyzenbeek Abrasion - Cotton Duck
50,000 cycles

Cold Crack -10°F

CFFA 6-a

UV Stabilized Pigments

QUV: ASTM D-4329 / CFFA-2 c2 - Grey Scale
650 hours



This fabric meets or exceeds these
ACT performance guidelines.

*Certification Marks owned by ACT®

Flame Retardancy*

California T.B. 117- 2013

FMVSS 302

IMO FTP 2010

Code MSC.307(88), Part 8, 3.1 & 3.2

NFPA 260 - Class I

UFAC - Class I

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics

Width: 54 in.

Roll Size: 30 yd.

Applications

Marine

Marine Interiors

RV

Brand

