



Content

Vinyl | Urethane Topcoat

Backing

Hi-Loft²™

Finish

PERMABLOK³®

Characteristics

Antifungal

Mildew Resistant

Stain Resistant

No Heavy Metals

Formaldehyde Free

Performance

Superior Abrasion

CFFA 1-a, ASTM D-4157
100,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -10°F

CFFA 6-a

UV Stabilized Pigments

QUV: ASTM D-4329 / CFFA-2 c2 - Grey Scale
650 hours



This fabric meets or exceeds these
ACT performance guidelines.

Certification Marks owned by ACT

Flame Retardancy*

California T.B. 117- 2013

FMVSS 302

IMO FTP 2010

Code MSC.307(88), Part 8, 3.1 & 3.2

NFPA 260 - Class I

UFAC - Class I

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics

Weight: 29 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications

Corporate

Restaurant

Hospitality

Sunroom

Marine

Auto | RV

Residential Interiors