



Content

100% Polyurethane

Backing

100% Polyester

Finish

PERMAGUARD®

Characteristics

Stain Resistant

No Heavy Metals

Formaldehyde Free

Polycarbonate Resin System

Performance

Superior Abrasion

CFFA 1-a, ASTM D-4157
300,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -10°F

CFFA 6-a

UV Stabilized Pigments

QUV: ASTM D-4329 / CFFA-2 c2
40 hours

Hydrolytic Stability

5 Year Hydrolysis



This fabric meets or exceeds these
ACT performance guidelines.
Certification Marks owned by ACT

Flame Retardancy*

California T.B. 117 - 2013

FMVSS 302

IMO FTP 2010

Code MSC.307(88), Part 8, 3.1 & 3.2

NFPA 260 - Class I

UFAC - Class I

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics

Weight: 21 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications

Corporate

Restaurant

Hospitality

Sunroom

Marine Interiors

Auto | RV

Residential Interiors