



Content

Vinyl | Urethane Topcoat

Backing

Ultra Hi-Loft^{2TM}

Finishes

PBG+ ^{PERMABLOK®}
^{PERMAGUARD®}

Characteristics

Antibacterial
AATCC TM 147

Mildew Resistant
ASTM G21

Pink Stain Resistant
ASTM E-1428

Stain Resistant
PQN M. 127-06

No Flame Retardants

No Phthalates

AB 2998 Compliant

Performance

Superior Abrasion
CFFA 1, ASTM D-4157-02
100,000 cycles, Wyzenbeek #10 Cotton Duck

UV Stability
XENOTEST: AATCC TM 16-3 / NTC 1479 /
CFFA-2 a1 - Blue Wool
1,000 Hours
QUV: ASTM D-4329 / CFFA-2 c2 - Grey Scale
650 Hours

Cold Crack -10°F
CFFA-6A



This fabric meets or exceeds these
ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*

California T.B. 117- 2013

NFPA 260 - Class I

UFAC - Class I

*This term and any corresponding data refers to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifics

Weight: 30 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications

- Automotive | RV
- Education
- Healthcare

Hospitality

- Hotel | Motel | Casino
- Restaurant
- Public Spaces

Marine

- Interior
- Exterior

Residential

- Interior
- Exterior