



Content

Vinyl | Urethane Topcoat

Backing

Hi-Loft²™

Finish

PERMABLOK³®



Characteristics

- Antibacterial
- Antifungal
- Stain Resistant
- No Heavy Metals
- Formaldehyde Free

Performance

Superior Abrasion
CFFA 1-a, ASTM D-4157
100,000 cycles, Wyzenbeek #10 Cotton Duck

Cold Crack -10°F
CFFA 6-a

UV Stabilized Pigments
Xenotest: AATCC Blue Wool
1,000 hours



This fabric meets or exceeds these ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*

- California T.B. 117 - 2013
- FMVSS 302
- IMO FTP 2010
Code MSC.307(88), Part 8, 3.1 & 3.2
- NFPA 260 - Class I
- UFAC - Class I
- Boston Fire Code
- Federal Aviation Specification
- Federal ST. 191A M 5903.1
- Port Authorities of NY & NJ

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

All Spradling International's vinyl- and PU- coated fabrics contain flame retardant additives.

Specifics

- Weight: 30 oz.
- Width: 54 in.
- Roll Size: 30 yd.

Applications

- Corporate
- Restaurant
- Hospitality
- Sunroom
- Marine
- Auto | RV
- Residential Interiors
- Healthcare