



Content

Vinyl | Urethane Topcoat

Environmental

Formulated free of
Flame and Biocide additives.

Backing

100% Polyester Hi-Loft²™

Finishes

PBG+ PERMABLOK®
PERMAGUARD

Characteristics

Ink and Stain Resistant
PLTM 1120 PQN M

Anti-static
ASTM D-257

Sulfide Stain Resistant
Fisher Body TM 31-12

Performance

Superior Abrasion
CFFA 1, ASTM D-4157-02
100,000 cycles, Wyzenbeek #10 Cotton Duck

UV Stability
Xenotest: AATC TM 16-3/ CFFA-2 A1
1,000 Hours

Cold Crack 14°F
CFFA-6A



This fabric meets or exceeds these
ACT performance guidelines.
*Certification Marks owned by ACT®

Flame Retardancy*

California T.B. 117 - 2013

NFPA 260 - Class I

UFAC - Class I

*This term and any corresponding data refer to the
typical performance in the specific tests indicated
and should not be construed to imply the behavior
of this or any other material under actual fire
conditions.

Our vinyls, when tested with suitable component
materials, may comply with California Technical
Bulletin 133.

Specifics

Weight: 32 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications

Automotive | RV

Education

Healthcare

Hospitality

Hotel | Motel | Casino

Restaurant

Theaters | Convention Centers

Marine

Interior

Exterior

Office

Residential

Interior

Exterior

